

*temporarily
+100 °C



REACH ✓
RoHS ✓

Non-reinforced hose with superior flexibility and durability

The flexible, durable and non-reinforced ToppFlex™ hoses are suitable for fuels and many oil based fluids. ToppFlex™ hoses are made of transparent ester based polyurethane. Therefore, they are not recommended for water.





We can manufacture ToppFlex™ in many colours upon request.

ToppFlex™ For fuels and many oil based fluids

Material: PUR (ester based polyurethane)
Structure: 1-layer non-reinforced hose
Colour: Transparent
Standards: Diameter and wall tolerances according to DIN16940



Technical information

 mm	+/-	 mm	 mm	+/-	 mm	50m	100m	title	packing	g/m
3	0,2	5	1	0,1	18	-	610030050100	3/5ToppFlex	coil	15
5	0,3	8	1,5	0,2	30	-	610050080100	5/8ToppFlex	coil	37
5,5	0,3	8	1,25	0,2	33	-	610055080100	5,5/8ToppFlex	coil	32
6	0,3	9	1,5	0,2	36	61006009050	-	6/9ToppFlex	coil	43,5
8	0,3	11	1,5	0,2	48	61008011050	-	8/11ToppFlex	coil	54
9	0,3	12	1,5	0,2	54	61009012050	-	9/12ToppFlex	coil	59
12	0,3	15	1,5	0,2	72	61012015050	-	12/15ToppFlex	coil	76